



TECHNICAL DATASHEET

GL-5

Typical properties :

| | | | | | | |
|--------------------|-----|-------|-------|-------|-------|--------|
| SAE | | 80W | 90 | 140 | 80W90 | 85W140 |
| Density at 15°C | | 0.893 | 0.904 | 0.905 | 0.895 | 0.907 |
| Viscosity Index | | 104 | 96 | 98 | 97 | 97 |
| Flash point | °C | 185 | 195 | 205 | 200 | 210 |
| Pour point | °C | -15 | - 18 | - 12 | - 30 | - 15 |
| Viscosity at 40°C | cSt | 77.1 | 195.2 | 362 | 138 | 365 |
| Viscosity at 100°C | cSt | 9.7 | 17.4 | 25.6 | 13.9 | 26.0 |

- Specifications :**
- API GL-5
 - MIL-L-2105B (mono) ; MIL-L-2105D (multi) ;
 - ZF TE-ML 01/05/08

General information:

Hypoid gear oil to be used in heavily charged transmissions for cars. Lubrication of heavily charged gear transmissions that require special anti-wear protection. Offers excellent protection against wear under heavy working conditions. High thermal stability. Good oxidation resistance. Even under heavy shockloads the very stable lubricant film gives optimal protection.